

NAVLAM SANDBLASTED™ Uncover Timbers Elegance, Embrace Laminates Strength



For more information

T 02 9457 9622 reception@newageveneers.com.au newageveneers.com.au



NAVLAM Sandblasted[™] is the ultimate pre-finished reconstructed timber veneer. Combining the warmth and texture of solid timber with the functionality, durability, and resilience of a laminate with an acrylic polyurethane finish, NAVLAM Sandblasted[™] is the ideal choice for any interior application. NAVLAM Sandblasted[™] panels deliver outstanding consistency across the grain and comes in an exciting range of colours, wood grains and panel sizes. Application is limited only by the imagination.

Technical & Design Advantages

As a reconstructed veneer, NAVLAM Sandblasted[™]delivers consistency in woodgrain structure and tone across each panel The veneer surface is finished with high quality, scratch and stain resistant 2-pac acrylic polyurethane finish and laid on a laminate back. NAVLAM Sandblasted[™] is available as a finished panel on your EO MR MDF substrate thickness of your choice, all décor colours have matching ABS (non-PVC) edging, making fabrication and installation simple and cost effective.

Environmental

NAVLAM Sandblasted[™] laminates and panels are an environmentally sustainable choice in pre-finished timber veneers. Our stringent sustainable sourcing criteria must be met, which includes strict forest management practices and sourcing veneers from controlled origin veneer suppliers.

Application

NAVLAM Sandblasted[™] comes ready for immediate fabrication or application. NAVLAM Sandblasted[™] is suitable for vertical installations and light-use horizontal applications such as shelving.

However, it is not recommended for high wear horizontal surfaces such as kitchen benchtops. The pre-finished surface contains a UV inhibitor to minimise discolouration caused by UV rays. To retain colour consistency, NAVLAM Sandblasted™ is not for use in areas with prolonged exposure to direct sunlight.

Edging

The NAVLAM Sandblasted[™] collection is supplied with matching, highly durable 1.0mm ABS (non-PVC) edging to achieve a range of edging profiles. Edging is also available in 22mm. 38mm and 54mm widths to suit a wide range of panel thicknesses. ABS Edging is not the same material make up as the face of the board. ABS Edging is subject to light refraction and may be perceived differently depending on light sources, light source locations and general environment that impacts finished visibility. Each ABS edging décor match has been stringently reviewed and approved to New Age Veneers standard for sale. As such this is not classified as a product defect, edged on board samples are available on our website to view prior to order.

Grain Direction

NAVLAM Sandblasted ${}^{\rm TM}$ grain runs vertically along the length of the panel.

Guarantee

New Age Veneers Pty Ltd guarantees the intrinsic qualities of NAVLAM Sandblasted[™] laminates. Discoloration due to exposure to sunlight and ultraviolet rays cannot be considered a material defect. In the event of any dispute, the guarantee and liability of New Age Veneers Pty Ltd is limited to the replacement of any material shown to be defective. New Age Veneers Pty Ltd reserves the right to discontinue any designs or products without notice at any time.

Exposure To Sunlight

NAVLAM Sandblasted[™] laminates are reconstructed from natural timbers and will react to direct and indirect sunlight. The pre-finished surface contains a UV inhibitor that offers some protection against discolouration, but like all natural wood products, colour variation will occur over time. Excessive exposure to direct sunlight may cause timber veneers to undergo sudden and irregular colour changes.

Cleaning & Maintenance

NAVLAM Sandblasted[™] surfaces are easy to clean. Simply use a cloth dampened with warm water and detergent. If in doubt about a particular cleaning product or detergent, check with the manufacturer for suitability. Avoid the following when cleaning, as these substances and materials could damage the finish and make the surface susceptible to staining:

- Acetone or trichloroethylene
- Abrasive cleaners, harsh detergents, and powders
- Scouring pads, steel wool and sandpaper • Ceramic cooktop cleaners
- Bathroom and tile cleaners
- Oven cleaners
- Chlorine bleach

Accidental spills or splatters of any harsh substance should be wiped off immediately and the area cleaned thoroughly with a damp cloth.

Features & Benefits

- Supplied ready to fabricate (pre-finished board)
- Consistent colour and grain
- Scratch and abrasion properties
- Stain and water resistant
- Matching ABS edging

Applications

- Vertical installations and some low traffic horizontal applications (i.e. shelving)
- Commercial areas (i.e. reception areas, staff rooms, board rooms, workstations, storage joinery)
- Kitchen, bathroom and laundry joinery
- Furniture
- Restrooms
- Wall and ceiling linings

Fabrication

Before fabrication, check all panels for defects. Keep the plastic film on the panels during fabrication, only removing it once the product is installed. To cut Navlam Sandblasted™, use a CNC router, panel saw, or table saw. Routers for trimming edges must have a smooth, clean base plate to avoid scratching the veneer surface. When drilling into NAVLAM Sandblasted™ use standard wood bits, router bits or carbide-bits with ball bearing guide rolls, ensuring any drill bit used is sharp. For a final edge finishing, use a flat, smooth, or fine file. Please note: the use of contact adhesive will void any warranty Panels must only be laminated using a PUR adhesive.

NAVLAM Sandblasted[™] Decor Specifications

Decors	Grain Structure
Allura Ash	Crown Quarter Cut
Italian Oak	Crown Quarter Cut
Lamora	Rift Quarter Cut
Perla Nera	Crown

NAVLAM Sandblasted[™] List Price (Per M²)

EO MR MDF	18mm	20mm	27mm	34mm
G1S	\$187.20	\$188.39	\$203.90	\$215.82
G2S	\$298.10	\$306.44	\$314.79	\$326.71

Laminate - Nominal Thickness List Price (Per M2)

\$125.92 - 1mm only

NAVLAM Sandblasted[™] on NAVCORE[™] Falcatta Light Weight Blockboard (Per M²) 2980mm x 1200mm

NAVCORE™	40mm	52mm
G1S	\$272.94	\$285.45
G2S	\$360.56	\$379.33

Matching ABS Edging

(Unglued 50LM Rolls)

	(1mm
\$1.61 LM \$2.38 LM \$3.57 L	М

For full sheet images please refer to website

Matching ABS edging available

When using NAVLAM on board for doors and drawers NAV recommends the use of G2S boards only. NAV will not warrant any bowing issues that occur when purchasing Navlam G1S on board.

On Board Packaging and Freight Sydney Metro \$110.00 VIC. ACT. SA. Brisbane Metro \$130.00 WA, Far Nth QLD, NT, TAS, Country NSW|VIC|SA|QLD - POA

ABS Edging Packaging and Freight Metropolitan & Interstate \$60.00

Laminate Packaging and Freight Metropolitan & Interstate \$85.00 (Excluding WA - POA)

Pricelist effective as of February 2025 (Excluding GST)

Technical Specifications

Laminate only nominal sheet size: 3100mm x 1250mm x 1mm Panel sizes: 3000mm x 1200mm (Various E0 MR MDE thicknesses available). Bowed boards will only be recognised under the NAVLAM Sandblasted[™] Warranty if a full check was made prior to the boards being cut, edged, and installed. NAV will not warrant any bowing issues that may occur when purchasing NAVLAM Sandblasted[™] G1S on board due to unbalanced faces.



3000 x 1200mm Sheets



		_
		_





